

IN THE CLAIMS:

Please amend the claims as indicated below:

1. (Currently amended) A computer-implemented method for characterizing gene
5 expression, ~~comprising executing, via a computer, the following steps:~~ wherein the method is run
on a system comprising one or more distinct devices, each of the one or more distinct devices
being embodied on a tangible computer-readable recordable storage medium, the method
comprising:

determining a plurality of gene expression signals for a gene, wherein said
10 plurality of gene expression signals comprise control data and phenotype data, wherein
determining a plurality of gene expression signals for a gene is carried out by a data storage
device executing on a hardware processor;

transforming said control data, wherein transforming said control data comprises
transforming a probability density distribution for said control data to a uniform probability
15 density for said control data, wherein said transforming results in transformed control data
having a uniform distribution of said gene expression signals within a selected interval in said
control data, and wherein said transformed control data is applied to corresponding phenotype
data to convert said corresponding phenotype data to one or more transformed phenotype values,
wherein transforming said control is carried out by the data storage device executing on a
20 hardware processor;

using said one or more transformed phenotype values to determine one or more
gene expression patterns by searching said one or more transformed phenotype values for one or
more patterns, wherein searching comprises using a pattern-finding algorithm to determine the
one or more gene expression patterns, wherein using said one or more transformed phenotype
25 values to determine one or more gene expression patterns is carried out by the data storage
device executing on a hardware processor;

generating a model for a probability density function of an expression level for each of the one or more gene expression patterns of the phenotype data, wherein generating the model is carried out by the data storage device executing on a hardware processor;

characterizing gene expression of an unknown sample by using the model for the
5 probability density function of the expression level for each of the one or more gene expression patterns of the phenotype data to determine one or more gene expression patterns for said unknown sample and comparing said one or more gene expression patterns of said unknown sample with said one or more gene expression patterns that characterize said control data and said phenotype data to classify said unknown sample as similar to either said control data or said
10 phenotype data or neither, wherein characterizing gene expression of the unknown sample is carried out by the data storage device executing on a hardware processor; and

outputting said characterization to a user.

2. (Previously presented) The method of claim 1, further comprising the step of
15 transforming gene expression signals of an additional sample.

3. (Previously presented) The method of claim 1, wherein the step of transforming comprises the steps of:

determining a function that approximates a distribution of the plurality of gene
20 expression signals for the gene; and

using the function to transform said plurality of gene expression signals, wherein said transformed gene expression signals have a uniform distribution of said gene expression signals within a selected interval in said control data.

25 4. (Canceled)

5. (Canceled)

6. (Canceled)

5 7. (Canceled)

8. (Canceled)

9. (Canceled)

10

10. (Canceled)

11. (Canceled)

15

12. (Canceled)

13. (Canceled)

14. (Canceled)

20

15. (Canceled)

16. (Canceled)

25

17. (Previously Presented) A system comprising:

a memory that stores computer-readable code; and

a processor operatively coupled to the memory, the processor configured to
implement the computer-readable code, the computer-readable code configured to:

determine a plurality of gene expression signals for a gene, wherein said plurality of gene expression signals comprise control data and phenotype data;

transform said control data, wherein transforming said control data comprises transforming a probability density distribution for said control data to a uniform probability
5 density for said control data, wherein said transforming results in transformed control data having a uniform distribution of said gene expression signals within a selected interval in said control data, and wherein said transformed control data is applied to corresponding phenotype data to convert said corresponding phenotype data to one or more transformed phenotype values;

use said one or more transformed phenotype values to determine one or more
10 gene expression patterns by searching said one or more transformed phenotype values for one or more patterns, wherein searching comprises using a pattern-finding algorithm to determine the one or more gene expression patterns;

generate a model for a probability density function of an expression level for each of the one or more gene expression patterns of the phenotype data;

15 characterize gene expression of an unknown sample by using the model for the probability density function of the expression level for each of the one or more gene expression patterns of the phenotype data to determine one or more gene expression patterns for said unknown sample and comparing said one or more gene expression patterns of said unknown sample with said one or more gene expression patterns that characterize said control data and
20 said phenotype data to classify said unknown sample as similar to either said control data or said phenotype data or neither; and

output said characterization to a user.

18. (Previously presented) The system of claim 17, wherein the computer-readable code is
25 further configured to transform gene expression signals of an additional sample.

19. (Previously presented) The system of claim 17, wherein the computer-readable code is further configured, during the step of deriving, to perform the steps of:

determine a function that approximates a distribution of the plurality of gene expression signals for the gene; and

5 use the function to transform said plurality of gene expression signals, wherein said transformed gene expression signals have a uniform distribution of said gene expression signals within a selected interval in said control data.

20. (Canceled)

10 21. (Canceled)

22. (Canceled)

15 23. (Currently amended) An article of manufacture comprising:

a tangible computer readable recordable storage medium having computer readable code means embodied thereon, the computer readable program code means comprising:

a step to determine a plurality of gene expression signals for a gene, wherein said plurality of gene expression signals comprise control data and phenotype data;

20 a step to transform said control data, wherein transforming said control data comprises transforming a probability density distribution for said control data to a uniform probability density for said control data, wherein said transforming results in transformed control data having a uniform distribution of said gene expression signals within a selected interval in said control data, and wherein said transformed control data is applied to corresponding
25 phenotype data to convert said corresponding phenotype data to one or more transformed phenotype values;

a step to use said one or more transformed phenotype values to determine one or

more gene expression patterns by searching said one or more transformed phenotype values for one or more patterns, wherein searching comprises using a pattern-finding algorithm to determine the one or more gene expression patterns;

a step to generate a model for a probability density function of an expression level
5 for each of the one or more gene expression patterns of the phenotype data;

a step to characterize gene expression of an unknown sample by using the model for the probability density function of the expression level for each of the one or more gene expression patterns of the phenotype data to determine one or more gene expression patterns for said unknown sample and comparing said one or more gene expression patterns of said unknown
10 sample with said one or more gene expression patterns that characterize said control data and said phenotype data to classify said unknown sample as similar to either said control data or said phenotype data or neither; and

a step to output said characterization to a user.

15 24. (Previously presented) The article of manufacture of claim 23, wherein the computer-readable code means further comprises a step to transform gene expression signals of an additional sample.

20 25. (Previously presented) The article of manufacture of claim 23, wherein the computer-readable code means is further configured, during the step of deriving, to perform:

a step to determine a function that approximates a distribution of the plurality of gene expression signals for the gene; and

a step to use the function to transform said plurality of gene expression signals, wherein said transformed gene expression signals have a uniform distribution of said gene
25 expression signals within a selected interval.

26. (Canceled)

27. (Canceled)

28. (Canceled)

5

29. (Previously presented) The method of claim 1, wherein the selected interval comprises an interval between 0 and 1.